

Adhesive Specialities

Manufacturer of Speciality Adhesive Tapes

TECHNICAL DATA SHEET

Product Code - AS-055-A

MASKING LIQUID - BOOTH COAT

Description: Masking Liquid – Booth Coat is a temporary clear coating for spray painting booth's walls, ceiling, floor and other surfaces where accumulated paint over-spray can be removed easily. Booth Coat can also be used as a coating for steel surfaces to eliminate flash rusting or as protection on glass, plexiglass, rubber, cement, aluminium and many such hard surfaces.

Booth Coat represents the ultimate in non-solvent coatings as it is well stabilized against brittleness and will not be softened or penetrated by most solvent-based paints. Booth Coat has no Volatile Organic Compounds (VOCs).

Application: Booth Coat can cause problems if applied wrongly and proper application results in a tough film of uniform thickness with no sagging, less application time and minimal clean-up. Waterborne clear peel-able coating can be used wherever temporary protective coatings are needed to reduce clean-up problems. Booth Coat can be used in spray-booths, floors, windows, walls, machinery, equipment or wherever there is paint over-spray problem, clean-up problem or an emission problem.

Application Technique: For best results, ensure the surface is clean, dry and dust free before application of the tape. Apply even and firm pressure for better adhesion results.

Storage & Shelf Life: The tape should be stored in a cool and dry place and prolonged exposure to the direct sunlight should be avoided. To obtain best performance, the product should be used within 12 months from the manufacturing date.

www.adhesivespecialities.co.in

©Adhesive Specialities