

**SUN BRAND**Securely *Sealing* Sentiments  
An ISO CERTIFIED COMPANY

# Adhesive Specialities

*Manufacturer of Speciality Adhesive Tapes*

## TECHNICAL DATA SHEET

**Product Code – AS – 068****DOUBLE SIDE PE FOAM – 2.0 MM**

**Description:** Double Side PE Foam Tape is made out of PE foam coated with hotmelt adhesive giving it a good adhesion, high shear strength and long aging properties. PE Foam tape is also available with paper, PVC or PE Liner.

**Application:** Double Side PE Foam Tape is with excellent strong adhesion to be used in automotive interiors and permanent bonding of light-weight materials.

**Application Technique:** For best results, ensure the surface is clean, dry and dust free before application of the tape. Even and firm pressure to be applied for better adhesion results.

## TECHNICAL VALUES

Properties	Value
Base Material	PE Foam – 2.0 mm
Adhesive	Hotmelt
Coating Thickness	70 gsm
Total Thickness	2 mm
Tensile Strength (lbs/inch)	72 gms / 25 mm
Elongation	284 MD ± 10 %
Adhesion to Steel (gms/inch)	1,100 gms
Heat Resistance (°C/hr.)	-10 ~ 90 °C
Density	64 kg / m <sup>3</sup>
Hardness	30 / 40 Shore C
Release Liner	PVC / Paper / PE
Available Colour	White / Black

**Storage & Shelf Life:** The tape should be stored in cool and dry place and prolonged exposure to the direct sunlight should be avoided. To obtain best performance, the product should be used within 12 months from the date of manufacture.

[www.adhesivespecialities.co.in](http://www.adhesivespecialities.co.in)

The technical values are determined by/based on standard tests. Our recommendations on the use of the product are based on reliable in-house tests, but the users are requested to conduct their own test to determine the suitability of the product. Adhesive Specialities will not be responsible for any loss or damage caused as a result of our recommendations!

© ADHESIVE SPECIALITIES