



**SUN BRAND**

Securely *Sealing* Sentiments  
An ISO CERTIFIED COMPANY

# Adhesive Specialities

*Manufacturer of Speciality Adhesive Tapes*

TECHNICAL DATA SHEET

**Product Code – AS-003**

## **ALUMINIUM FOIL + LDPE LAMINATED TAPE**

**Description:** Aluminium Foil + LDPE Laminated Tape is 20 micron aluminium foil is laminated with 50 micron LDPE film. The tape comes without liner and glue.

**Application:** Aluminium Foil + LDPE Laminated Tape is used in various die-cuts sticker application in automotive industries. The minimum recommended application temperature is 4°C to 40°C.

**Application Technique:** For best results, ensure the surface is clean, dry and dust free before application of the tape. Apply even and firm pressure for better adhesion results.

### **TECHNICAL VALUES**

<b>PROPERTIES</b>	<b>VALUES</b>
Base Material	Aluminium Foil - 20µm ± 2 µm LDPE Film – 50 µm
Total Thickness	90 µm
Tensile Strength (kg/mm)	10.0 kgs/25mm
Elongation (%)	10 %

**Storage & Shelf Life:** The tape should be stored in a cool and dry place and prolonged exposure to the direct sunlight should be avoided. To obtain best performance, the product should be used within 12 months from the manufacturing date.

[www.adhesivespecialities.co.in](http://www.adhesivespecialities.co.in)

©Adhesive Specialities

The technical values are determined by/based on standard tests. Our recommendations on the use of the product are based on reliable in-house tests, but the users are requested to conduct their own test to determine the suitability of the product. Adhesive Specialities will not be responsible for any loss or damage caused as a result of our recommendations.