



SUN BRAND

Securely *Sealing* Sentiments
An ISO CERTIFIED COMPANY

Adhesive Specialities

Manufacturer of Speciality Adhesive Tapes

TECHNICAL DATA SHEET

Product Code – AS-003

Aluminum Foil + LDPE LAMINATED TAPE

Description: Aluminum + LDPE Laminated Tape is 20 mic aluminum foil laminated with 50 mic LDPE. The tape comes without liner and glue.

Application: Aluminum Foil + LDPE Laminated Tape is used in various die cuts sticker application in automotive industries. The minimum recommended application temperature is 4 to 40 .

Application Technique: For best results, ensure the surface is clean, dry and dust free before application of the tape. Apply even and firm pressure for better adhesion results.

Technical Values

PROPERTIES	VALUE
Base Material	Aluminum Foil – 20 μm \pm 2 μm LDPE Film – 50 μm
Total Thickness	90 μm \pm 2 μm
Tensile Strength (kgs/mm-width)	10 kgs / 25 mm
Elongation (% at break)	10%

Storage & Shelf Life: The tape should be stored in cool and dry place and prolonged exposure to the direct sunlight should be avoided. To obtain best performance, the product should be used within 12 months from the date of manufacture.

www.adhesivespecialities.co.in

The technical values are determined by/based on standard tests. Our recommendations on the use of the product are based on reliable in-house tests, but the users are requested to conduct their own test to determine the suitability of the product. Adhesive Specialities will not be responsible for any loss or damage caused as a result of our recommendations!

© ADHESIVE SPECIALITIES