



SUN BRAND

Securely *Sealing* Sentiments
An ISO CERTIFIED COMPANY

Adhesive Specialities

Manufacturer of Speciality Adhesive Tapes

TECHNICAL DATA SHEET

Product Code – AS-014

ANTI SLIP/SKID TAPE

Description: Anti Slip/Skid Tape is made from a special water and solvent proof material. The sand blasting of anti-skid particles is done on the material to achieve 80 Poise (80 granules per square inch) to ensure the durability of the tape for a long time after use. The tape is available in black, black & yellow and transparent colors. Minimum order quantity is required for any other special color.

Application: Anti Slip/Skid Tape is primarily used to make a surface slip resistant to prevent slipping/skidding on dry, wet, oily floors in industrial and commercial areas such as corridors, production and storage rooms, ramps, stairways, ladders, footplates on machines, emergency exits etc.

Application Technique: For best results, ensure the surface is clean, dry and dust free before application of the tape. Apply even and firm pressure for better adhesion results.

TECHNICAL VALUES

PROPERTIES	VALUES
Base Material	PET Film – 50 μ m
Adhesive	Acrylic
Total Thickness	70 – 80 μ m
Granularity	80 #
Sand Layer	Aluminium Oxide
Product Weight	0.78 kg/m ²
Holding Power (hr.)	> 48 hrs.
Co-efficient of Friction	R<13
Tensile Strength (kg/25mm)	1.73 kgs
Roll Ball Tack	10 cms
Release Liner	Silicon Paper – 150 μ m

Storage & Shelf Life: The tape should be stored in cool and dry place and prolonged exposure to the direct sunlight should be avoided. To obtain best performance, the product should be used within 12 months from the date of manufacture.

www.adhesivespecialities.co.in

©Adhesive Specialities

The technical values are determined by/based on standard tests. Our recommendations on the use of the product are based on reliable in-house tests, but the users are requested to conduct their own test to determine the suitability of the product. Adhesive Specialities will not be responsible for any loss or damage caused as a result of our recommendations.