



**SUN BRAND**

Securely *Sealing* Sentiments  
An ISO CERTIFIED COMPANY

# Adhesive Specialities

*Manufacturer of Speciality Adhesive Tapes*

TECHNICAL DATA SHEET

**Product Code – AS-017**

## **BLUE HOLDING TAPE**

**Description:** Blue Holding Tape is polyester film coated with natural rubber adhesive which gives it a high holding power without leaving any residue on removal.

**Application:** Blue Holding Tape is widely used for holding of components in the white goods industry.

**Application Technique:** For best results, ensure the surface is clean, dry and dust free before application of the tape. Apply even and firm pressure for better adhesion results.

## **TECHNICAL VALUES**

<b>PROPERTIES</b>	<b>VALUE</b>
Base Material	Polyester Film – 36 µm ±4 µm
Coating Thickness	25 µm ±4 µm
Total Thickness	60 µm
Adhesive	Natural Rubber
Elongation (% at break)	40%
Adhesion to Steel (g/inch)	950 gms
Tensile Strength (kg/inch)	9.0 kgs
Temperature Resistance (°C/hr.)	Adhesive: 130°C
Colour	Translucent Blue

**Storage & Shelf Life:** The tape should be stored in a cool and dry place and prolonged exposure to the direct sunlight should be avoided. To obtain best performance, the product should be used within 12 months from the manufacturing date.

[www.adhesivespecialities.co.in](http://www.adhesivespecialities.co.in)

©Adhesive Specialities

The technical values are determined by/based on standard tests. Our recommendations on the use of the product are based on reliable in-house tests, but the users are requested to conduct their own test to determine the suitability of the product. Adhesive Specialities will not be responsible for any loss or damage caused as a result of our recommendations.