



SUN BRAND

Securely *Sealing* Sentiments
An ISO CERTIFIED COMPANY

Adhesive Specialities

Manufacturer of Speciality Adhesive Tapes

TECHNICAL DATA SHEET

Product Code – AS-019

CELLULOSE TAPE

Description: Cellulose Tape is manufactured from cellulose film which is a wood based product of regenerated pulp. This clear transparent tape is coated with specially formulated rubber resin adhesive.

Application: Cellulose Tape is used for sealing of plastic bags, small boxes, lightweight cartons, gift and hamper wrapping, air tight sealing of can lids, glass container, textile packaging, scree printing etc. It is sometimes also used as antistatic tape application.

Application Technique: For best results, ensure the surface is clean, dry and dust free before application of the tape. Apply even and firm pressure for better adhesion results.

TECHNICAL VALUES

PROPERTIES	VALUE
Base Material	Cellulose Film – 25 µm
Adhesive	Rubber
Total Thickness	50 µm
Elongation (% at break)	180%
Adhesion to Steel (g/25mm)	> 550 gms
Colour	Transparent

Storage & Shelf Life: The tape should be stored in a cool and dry place and prolonged exposure to the direct sunlight should be avoided. To obtain best performance, the product should be used within 12 months from the manufacturing date.

www.adhesivespecialities.co.in

©Adhesive Specialities

The technical values are determined by/based on standard tests. Our recommendations on the use of the product are based on reliable in-house tests, but the users are requested to conduct their own test to determine the suitability of the product. Adhesive Specialities will not be responsible for any loss or damage caused as a result of our recommendations.