

**SUN BRAND**Securely *Sealing* Sentiments  
An ISO CERTIFIED COMPANY

# Adhesive Specialities

*Manufacturer of Speciality Adhesive Tapes*

## TECHNICAL DATA SHEET

**Product Code – AS-124**

### ELECTROPLATING TAPE – PVC

**Description:** Electroplating Tape is a premium grade tape that exhibits excellent adhesion, tack and good cohesion strength. The specially formulated rubber adhesive coating to PVC film gives it a high adhesion. The tape has a good resistance to solvent, chemicals and water.

**Application:** Electroplating Tape is mainly used as a masking tape for electroplating and anodizing application.

**Application Technique:** For best results, ensure the surface is clean, dry and dust free before application of the tape. Apply even and firm pressure for better adhesion results.

### TECHNICAL VALUES

PROPERTIES	VALUES
Base Material	PVC Film – 115 $\mu$ m
Adhesive	Rubber
Total Thickness	150 $\mu$ m
Tensile Strength (kg/in)	9 kgs
Adhesion to Steel (gms/in)	600 gms
Roll Ball Tack	6 cms
Temperature Resistance ( $^{\circ}$ C/hr.)	100 $^{\circ}$ C
Colours Available	Blue

**Storage & Shelf Life:** The tape should be stored in a cool and dry place and prolonged exposure to the direct sunlight should be avoided. To obtain best performance, the product should be used within 12 months from the manufacturing date.

[www.adhesivespecialities.co.in](http://www.adhesivespecialities.co.in)

©Adhesive Specialities

The technical values are determined by/based on standard tests. Our recommendations on the use of the product are based on reliable in-house tests, but the users are requested to conduct their own test to determine the suitability of the product. Adhesive Specialities will not be responsible for any loss or damage caused as a result of our recommendations.