



SUN BRAND

Securely *Sealing* Sentiments
An ISO CERTIFIED COMPANY

Adhesive Specialities

Manufacturer of Speciality Adhesive Tapes

TECHNICAL DATA SHEET

Product Code – AS-039 – D

EPDM FOAM TAPE – 6.0 MM – SINGLE SIDE

Description: EPDM Foam Tape is EPDM rubber coated with hotmelt adhesive and has good adhesion with high shear strength and long aging properties. EPDM Foam Tape is available in single side and double side.

Application : EPDM Foam Tape is suitable for glazing purpose, gap filling and insulation in panel applications. It is also often used in door seals, window seals, trunk seals, and hood seals.

Application Technique: For best results, ensure the surface is clean, dry and dust free before application of the tape. Apply even and firm pressure for better adhesion results.

Technical Values

Properties	Value
Base Material	EPDM Foam – 6.0 mm
Adhesive	Hotmelt
Base thickness	550 gsm
Total thickness	670 gsm
Tensile Strength	195 gms
Elongation	100 %
Adhesion to Steel (gms/inch)	1,000 gms
Heat Resistance (°C/hr.)	-10 °C ~100 °C
Hardness	27± 3 Shore A
Density	100 kg / m ³ ± 10 % kg / m ³
Release Liner	Paper

Storage & Shelf Life: The tape should be stored in cool and dry place and prolonged exposure to the direct sunlight should be avoided. To obtain best performance, the product should be used within 12 months from the date of manufacture.

www.adhesivespecialities.co.in

The technical values are determined by/based on standard tests. Our recommendations on the use of the product are based on reliable in-house tests, but the users are requested to conduct their own test to determine the suitability of the product. Adhesive Specialities will not be responsible for any loss or damage caused as a result of our recommendations!

© ADHESIVE SPECIALITIES