



SUN BRAND

Securely *Sealing* Sentiments
An ISOCERTIFIED COMPANY

Adhesive Specialities

Manufacturer of Speciality Adhesive Tapes

TECHNICAL DATA SHEET

Product Code – AS-058

MASKING TAPE – 02

Description: Masking Tape 02 is a general-purpose masking tape coated with acrylic emulsion adhesive. It resists solvents or water from the paint, yet can be removed cleanly without damaging the surface. The crepe paper backing can conform to curved and irregular surface for critical paint masking applications.

Application: Masking Tape 02 is used in paint masking application. The tape is easy to tear by hand for tool-free application. Other applications are protecting, labelling, painting, arts and crafts.

Application Technique: For best results, ensure the surface is clean, dry and dust free before application of the tape. Apply even and firm pressure for better adhesion results.

TECHNICAL VALUES

PROPERTIES	VALUES
Base Material	Crepe Paper – 55 gsm
Adhesive	Acrylic Emulsion
Total Thickness	120 µm
Tensile Strength (kg/25mm)	5.5 kgs
Elongation (% at break)	12%
Adhesion to Steel (gms/inch)	400 gms
Temperature Resistance (°C/hr.)	60°C
Roll Ball Tack	8 cms

Storage & Shelf Life: The tape should be stored in a cool and dry place and prolonged exposure to the direct sunlight should be avoided. To obtain best performance, the product should be used within 12 months from the manufacturing date.

www.adhesivespecialities.co.in

©Adhesive Specialities

The technical values are determined by/based on standard tests. Our recommendations on the use of the product are based on reliable in-house tests, but the users are requested to conduct their own test to determine the suitability of the product. Adhesive Specialities will not be responsible for any loss or damage caused as a result of our recommendations.