



SUN BRAND

Securely *Sealing* Sentiments
An ISOCERTIFIED COMPANY

Adhesive Specialities

Manufacturer of Speciality Adhesive Tapes

TECHNICAL DATA SHEET

Product Code – AS-059

MASKING TAPE - 04

Description: Masking Tape 04 is a general-purpose masking tape coated with hotmelt adhesive. This adhesive tape is easy to use and it's suitable for wood industries recommended for general indoor use at steady temperature. It sticks well to multiple and irregular surface and is compatible with both solvent and water based paints. It is easy-tear by hand and assures quick and easy removal.

Application: Masking Tape 04 is a low cost general purpose masking adhesive tape. The tape has very good sheer adhesion to specially design for wood industries. The tape is easy to tear by hand for tool-free application. Other applications are automotive holding, protecting, labelling, painting, arts and crafts.

Application Technique: For best results, ensure the surface is clean, dry and dust free before application of the tape. Apply even and firm pressure for better adhesion results.

TECHNICAL VALUES

PROPERTIES	VALUES
Base Material	Crepe Paper – 55gsm
Adhesive	Hotmelt Adhesive
Total Thickness	120 µm
Tensile Stress (kg/25mm)	4.5 kgs
Elongation (% at break)	17%
Adhesion to Steel (g/25mm)	980 gms
Temperature Resistance (°C/hr.)	60°C
Roll Ball Tack	8 cms

Storage & Shelf Life: The tape should be stored in a cool and dry place and prolonged exposure to the direct sunlight should be avoided. To obtain best performance, the product should be used within 12 months from the manufacturing date.

www.adhesivespecialities.co.in

©Adhesive Specialities

The technical values are determined by/based on standard tests. Our recommendations on the use of the product are based on reliable in-house tests, but the users are requested to conduct their own test to determine the suitability of the product. Adhesive Specialities will not be responsible for any loss or damage caused as a result of our recommendations.