



SUN BRAND

Securely *Sealing* Sentiments
An ISO CERTIFIED COMPANY

Adhesive Specialities

Manufacturer of Speciality Adhesive Tapes

TECHNICAL DATA SHEET

Product Code – AS-103-D

SURFACE PROTECTION TAPE – 40 mic – MILKY WHITE

Description: Surface Protection Tape (SPT) is made from milky white 40 micron LDPE film coated with acrylic emulsion adhesive. Self-Adhesive SPT has excellent protection against damages and scratches. The tape has adjustable peel force with no adhesive residue and weather as well as UV resistant.

Application: Surface Protection Tape is suitable for acrylic sheet, aluminium profiles, stainless steel sheets, GI coils and foam boards etc.

Application Technique: For best results, ensure the surface is clean, dry and dust free before application of the tape. Apply even and firm pressure for better adhesion results.

TECHNICAL VALUES

PROPERTIES	VALUE
Base Material	LDPE Film – 40 µm
Adhesive	Acrylic Emulsion
Total Thickness	40 ±5 µm
Tensile Strength (kg/25mm)	3.0 kgs
Elongation (% at break)	300%
Adhesion to Steel (g/inch)	180 gms
Temperature Resistance (°C/ hr.)	Adhesive: 60 °C

Storage & Shelf Life: The tape should be stored in a cool and dry place and prolonged exposure to the direct sunlight should be avoided. To obtain best performance, the product should be used within 12 months from the manufacturing date.

www.adhesivespecialities.co.in

©Adhesive Specialities

The technical values are determined by/based on standard tests. Our recommendations on the use of the product are based on reliable in-house tests, but the users are requested to conduct their own test to determine the suitability of the product. Adhesive Specialities will not be responsible for any loss or damage caused as a result of our recommendations.